

TECHNICAL DATA SHEET



SEISPRO®

Seismic Emulsion

Properties

SDS
#1146

Energy^a (cal/g)	1,000
Gas Volume^a (moles/kg)	35.5
Velocity^b (m/sec)	5,900
(ft/sec)	19,350
Detonation Pressure^b (Kbars)	103
Density (g/cc)	1.18
Water Resistance	Excellent

^aAll Dyno Nobel Inc. energy and gas volume values are calculated using PRODET™, the computer code developed by Dyno Nobel Inc. for its exclusive use. Other computer codes may give different values.

^bUnconfined 2 ¼ diameter x 4.4 lb charge.

Use Caution When Sleep Time Is Anticipated

A loaded hole that is not shot immediately after the detonator tests positive with a ShotPoint Tracker™ or other testing device could fail for reasons beyond the control of the drill crew and product manufacturer. Reasons for failure could include but are not limited to geologic shifting, lightning, vandalism, farmer or animal interference.

Hazardous Shipping Description

- Explosive, Blasting, Type E 1.1D UN 0241 II



PRODUCT DESCRIPTION

SEISPRO is a seismic emulsion explosive specifically designed for the harsh Canadian winter environment. With a high rate of detonation, SEISPRO produces an excellent elastic wave profile and is environmentally friendly: NO perchlorates or molecular explosives and benign products of detonation (water vapor, carbon dioxide and nitrogen). Designed for geophysical exploration, SEISPRO desensitizes more quickly than conventional, molecular explosives.



APPLICATION RECOMMENDATIONS

- **NEVER** use Dyno Nobel seismic explosive products and/or components with explosive products and/or components made by other manufacturers.
- **ALWAYS** use the Dyno Nobel high strength seismic detonator for optimum results.
- **ALWAYS** use built-in cap wells for seismic detonators. Two detonators are recommended for insurance and reliability where extreme environmental conditions are encountered.
- **NEVER** use light core load "Cut to Fit" (10 gains/foot, 2.2 gm/m) detonating cord.
- In-hole service life in water filled boreholes: 3 months in unpunctured plastic shell.
- Recommended temperature range is -20°C to 65°C (0°F to 150°F). For temperatures below 0°F (-20°C), a sleep (warm-up) time of 4 hours is recommended before detonation.

Product Disclaimer: Please see reverse side.

DYNO
Dyno Nobel

TECHNICAL DATA SHEET



SEISPRO®

Seismic Emulsion

IMPORTANT! Ignoring these warnings may result in injury or death!

- **ALWAYS** exercise extreme caution when approaching a shothole that has not vented. Venting gases after detonation are common. BLOWOUTS CAN INJURE OR KILL.
- **NEVER** attempt to alter the product by cutting, sawing or disassembly of the package.
- **NEVER** drop load explosive into a borehole.
- **NEVER** attempt to dislodge explosives by pushing with a drill stem.
- **ALWAYS** shunt electric detonators and/or the blast circuit after testing and keep shunted until connected to blasting machine.
- **NEVER** unshunt electric detonators prior to use except to test with blasting galvanometer.
- **ALWAYS** ask if you don't know before proceeding.

Packaging

SEISPRO is available in a plastic shell.

Part Number	Nominal Unit Size	Package Style
IL 50437125E	36 mm (1.4 in) x 1/8 kg (.275 lb)	Plastic Shell
IL 50437250	36 mm (1.4 in) x 1/4 kg (.55 lb)	Plastic Shell
IL 50457001	60 mm (2.4 in) x 1.0 kg (2.2 lb)	Plastic Shell
IL 50460100E	60 mm (2.4 in) x 1.0 kg (2.2 lb) Coupled	Plastic Shell

TRANSPORTATION, STORAGE AND HANDLING

- SEISPRO must be transported, stored, handled and used in conformity with all applicable federal, state, provincial and local laws and regulations.
- Packaged emulsions have a shelf life of one (1) year when stored at temperatures between -18° C and 38° C (0° F and 100° F). Explosive inventory should be rotated. Avoid using new materials before the old. For recommended good practices in transporting, storing, handling and using this product, see the booklet "Prevention of Accidents in the Use of Explosive Materials" packed inside each case and the Safety Library Publications of the Institute of Makers of Explosives.

ADDITIONAL INFORMATION – Visit dynonobel.com for Brochures and Case Studies related to this product.

Product Disclaimer: Dyno Nobel Inc. and its subsidiaries disclaim any warranties with respect to this product, the safety or suitability thereof, or the results to be obtained, whether express or implied, INCLUDING WITHOUT LIMITATION, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE AND/OR OTHER WARRANTY. Buyers and users assume all risk, responsibility and liability whatsoever from any and all injuries (including death), losses, or damages to persons or property arising from the use of this product. Under no circumstances shall Dyno Nobel Inc. or any of its subsidiaries be liable for special, consequential or incidental damages or for anticipated loss of profits.

DYNO®
Dyno Nobel